


# Assembleon

Leaders in Electronic Manufacturing Technology



January 2006

## MG-8 SPECIFICATIONS

**PA 1318/01 MG-8 CL**  
**PA 1318/02 MG-8 CLi**  
**PA 1318/03 MG-8 ITF**

© Assemblée 2006

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is to be believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.

Publication thereof does not convey nor imply license under patent or other industrial or intellectual property rights.

“Values are valid at specified conditions”.

Date of release: January 2006

9498 392 0031.1

# *Assembleon*

Leaders in Electronic Manufacturing Technology

<b>Contents</b>		
1.0	Introducing the MG-8	3
2.0	General Specifications	5
3.0	Features, Accessories and Options	10
3.1	Features	10
3.2	Accessories and Options	12
3.3	Machine Configuration Examples	14
4.0	Mounting Head	20
4.1	Configuration Head MG-8	20
4.2	Force Control (PA 1902/00)	21
5.0	Alignment	22
5.1	Line Array Camera Alignment	22
5.2	Single Area CCD Alignment (PA 2969/88)	23
5.3	Side View Camera (PA 2969/45)	24
5.4	3D Vision System (PA 2969/35, PA 2969/36)	25
5.5	Fiducial Alignment	27
5.5	Master Bad Mark Sensing	29
6.0	Board Handling	30
6.1	Automatic Nozzle Exchange Station (PA 2463/28)	34
6.2	Nozzle Cleaning Station	35
7.0	Component Feeding	36
7.1	Smart Feeders CLi	36
7.2	Smart Feeder ITF	37
7.3	Feeder Indicators	39
7.4	Double Shuttle Tray Sequencer (PA 2699/25)	39
7.5	Single ATS Tray Feeder (PA 2696/27)	41

7.6	Double ATS Tray Feeder (PA 2696/28)	43
7.7	Pallet Indicators	44
7.8	Mountable Components & Required Nozzles MG-8	45
8.0	Feederbar Exchange System	48
8.1	Feeder Exchange System 24 pos. CLi PA 2505/70	48
8.2	Feeder Exchange System 24 pos. CL PA 2505/75	49
8.3	Feeder Exchange System 20 pos. ITF PA 2505/52	50
9.0	MG-8 Summary	52

## 1.0 Introducing the MG-8

The MG-8, the new generation High Speed Multifunctional Production Machine, belongs to the top-of-the-line Assembléon SMD pick & place machines.

With the MG-8 a feeder commonality between all Assembléon machines has been continued which increases the MG-8 flexibility.

The MG-8 is a high mix and high accuracy multifunctional machine that can handle a wide range of components at speeds up to 8,300 SMDs per hour. The machine is built around a very rigid, vibration-free frame for improved accuracy and long-term stability and is perfectly suitable for round-the-clock production.




Figure 1 Front view MG-8

The MG-8 features a high precision placement beam carrying three fully servo-controlled FNC (Flying Nozzle Change) heads, each equipped with six nozzles. The placement beam moves in X/Y and Z direction, while the board and component feeders are stationary. A flexible board transport system enables the MG-8 to handle virtually any type of PCB with the use of a double board clamping system. Board conveyor width is automatically adjustable, allowing board dimensions up to 460 x 440mm (18" x 17.2") to be handled.

The newly designed digital vision system with Line Array camera allows fast and accurate "on-the-fly" alignment of a wide range of components from 01005 (0402) up to 45x 100mm.

Dark or white background BGAs,  $\mu$ BGAs and CSPs with ball pitches down to 0.4mm (16 mil) and ball diameters down to 0.1 mm (4 mil) can be recognized by the newly developed illumination unit which allows measurement of ball positions and dimensions.

The vision system detects missing, bent or irregular spaced leads or BGA balls; faulty components are rejected. Optional Single area CCD camera extend the component range to 55mm square BGAs with ball pitches down to 0.4mm (16 mil).

A separate camera system monitors fiducial marks at the board, circuit and component level, using a combination of white-light and IR LEDs with multi-angle diffusers to provide optimal illumination.

Just six nozzle shapes are required to cover the specified SMD range. High output levels are therefore achieved, as the need for nozzle exchanges is minimal. Optionally a 18 position nozzle exchange station enables additional special nozzles (grippers) to be accommodated.

Up to 90 tape feeders can be loaded on the MG-8. The machine supports tape, stick, bulk and tray feeders. The tape feeder design for the MG-8 allows simultaneous picking from any mix of tape feeders ranging from 8 to 72 mm.

A Windows XP based controller, running a user-friendly Graphical User Interface, allows the MG-8 to be used stand-alone or in-line and can be easily hooked up to the external network. The controller includes a Management Information System (MIS) that continuously gathers production data for management feedback. The unique bad mark sensing capabilities allow a multi-circuit panel to be run as one large board, thus maximizing placement speed while still using bad mark information. A laser-based verification system, which guarantees correct feeder latching, is standard. Feeder indication lights helps the operator during set-up and operation.

Off-line feeder changeover can be achieved by using a 24 position Feederbar Exchange System (FES). An entire feederbar can be conveniently loaded off-line, minimizing change-over time.

A basic program optimization function is also included in the machine as standard which can be used during production. For more advanced line optimization the Advanced Manufacturing Suite AMS, allows you to create and optimize SMD machine programs on a PC instead of using the SMD machine. User interface from machine and AMS software are the same; therefore reducing training requirements.

## 2.0 General specifications

MG-8		
		REMARKS
Tact time:	0.43 sec/chip with line array camera 0.6 sec/QFP in normal mode with line array camera 0.8 sec/QFP in QFP mode with line array camera 1.5 sec/QFP with area CCD camera 2.0 sec/QFP with area CCD camera	Simultaneous pick with 3 heads Simultaneous pick with 3 heads Sequential pick with 3 heads Simultaneous pick with 3 heads Sequential pick
Optimal placement rate:	8,300 cph	Simultaneous pick with 3 heads
Tact time IPC 9850:	7,300 cph	
Nominal placement rate:	5,500- 6,000 cph	Real mounting time
Applicable Components:	01005 (0402) - SOP, SOJ, PLCC 32mm $\varnothing$ (1.26") 01005 (0402) - 20mm $\varnothing$ (0.79") with pin pitch down to 0.3mm (12 mil) 20mm - 32mm $\varnothing$ (0.79") with pin pitch down to 0.4mm (16 mil) BGA, $\mu$ BGA,CSP : 32mm $\varnothing$ : Min. ball pitch down to 0.4mm (16mil) Min. ball diameter down to 0.1mm (4mil) Irregularly shaped SMDs, 100mm x 32mm Maximum grid for BGA components is 64x64	Line array camera system (32mm)  Ball presence check for $\geq$ 0.1mm ball diameter Ball defect check for $\geq$ 0.2mm ball diameter
	0201(0603) - SOP, SOJ, PLCC 45mm $\varnothing$ (1.77") 0201 (0603)- 20mm $\varnothing$ (0.79") with pin pitch down to 0.3mm (12 mil) 20mm - 45mm $\varnothing$ (1.77") with pin pitch down to 0.4mm (16 mil) BGA, $\mu$ BGA,CSP: 45mm $\varnothing$ : Min. ball pitch down to 0.4mm (16mil) Min. ball diameter down to 0.15mm (6mil) Irregularly shaped SMDs, 100mm x 45mm Maximum grid for BGA components is 64x64	Line array camera system (45mm)  Ball presence check for $\geq$ 0.15mm ball diameter. Ball defect check for $\geq$ 0.3mm ball diameter.
	0402(1005) - SOP, SOJ, PLCC 45mm $\varnothing$ (1.77") 0402(1005) - 20mm $\varnothing$ (0.79") with pin pitch down to 0.3mm (12 mil) 20mm - 45mm $\varnothing$ (1.77") with pin pitch down to 0.4mm (16 mil) BGA, $\mu$ BGA,CSP: 55mm : Min. ball pitch down to 0.4mm (16mil) Min. ball diameter down to 0.15mm (6mil) Maximum grid for BGA components is 64x64	Digital area CCD camera (55mm $\varnothing$ )  Ball presence check for $\geq$ 0.15mm ball diameter. Ball defect check for $\geq$ 0.3mm ball diameter.
Component height:	Max: 25.5mm (1.00") Max: 20.0mm (0.79") in combination with the side view camera	Placing of higher parts is possible if certain conditions are met.
Mounting accuracy (X,Y) $\mu$ +3 $\sigma$ :	$\pm$ 50 $\mu$ for chips 01005-0201-0402 $\pm$ 75 $\mu$ for chips and SOIC (this is lead dependent) $\pm$ 30 $\mu$ for QFP's	Line array camera system (all placement heads and all placement angles, with special components and board)
Mounting accuracy ( $\varphi$ ) 3 $\sigma$ :	For Chips and SOIC this is lead dependent $\pm$ 0.1° for QFP's	Line array camera system (all placement heads and all placement angles)
Mounting repeatability X,Y 3 $\sigma$ :	15 $\mu$ for QFPs	
Mounting angle:	0 up to 360 (programmable in steps of 0.01)	



<b>MG-8</b>		
		<b>REMARKS</b>
Number of heads:	Three independent Flying Nozzle Change heads each equipped with 6 nozzles	One position of each head, can be equipped with a nozzle holder which can be used in combination with the nozzle exchange station
Alignment system:	Line array camera 45mm with illumination system for Vision on the Fly Second line array camera Side view camera for reliability and quality performance 3D camera for co-planarity check functionality Moving CCD camera for Fiducial alignment	Standard Optional Optional Optional Standard
Type of nozzles:	Type 221F Type 222F Type 223F Type 224F Type 225F Type 226F (Melf) Type 22W Special nozzle for 01005	Nozzle and feeder for 01005 on special request.
Nozzle exchange station:	18 nozzle positions	Optional, including 3 nozzle holders and 3 MELF nozzles type 226A
Component weight:	Max: 24 gr.	With nozzle type 225F
Nozzle cleaning station:	For all standard nozzle types and special 01005 nozzle	3 heads at one time
Component mounting interdistance:	01005-0402: 0.25mm or more Chip: 0.5mm or more SOP: 0.5mm or more QFP: 0.25mm or more	
Placement system:	Servo controlled for component height compensation	
Placement force:	0.23N/mm for spring loaded nozzles 5.7N for rigid nozzles	Pre-tension is 0.88N. (spring loaded)
	Programmable force control 10-40 Newton in steps of 0.1N	Optional force control unit
Number of feeders:	Pneumatic Tape Feeders Cl(i) type: 8mm: 96 feeders 12mm: 44 feeders 16mm: 44 feeders 24mm: 32 feeders 32mm: 28 feeders 44mm: 20 feeders 56mm: 16 feeders Stick feeders: Depends on stick dimensions Bulk feeders: 96 feeders	90 positions reachable  72mm Tape feeder is available on special request 90 positions reachable
Feeder indicators:	96 LED indicators (Green, Yellow & Red)	Standard (Not available for MG-8 with ITF feeder interface)

<b>MG-8</b>		
		<b>REMARKS</b>
Number of ITF feeders:	Intelligent Tape Feeders: 8mm: 40 feeders (80 code numbers with Twin tape feeder) 12mm: 18 feeders 16mm: 18 feeders 24mm: 20 feeders 32mm: 12 feeders 44mm: 10 feeders 56mm: 8 feeders Stick feeders: Depends on stick dimensions	Standard the MG-8 with ITF feeder interface is a single sided machine. Rear side ITF feederbar only on special request
Component Packaging:	Tape according to IEC/EIA-J/JEDEC: 8-56mm For larger tape feeders such as 72mm please contact your local sales representative	Tape reel diameter max: 380mm (15")
	Single ATS Tray Feeder: Max. tray size: 230mm x 335mm (9.1" x 13.2") Min tray size 90mm x 140mm (3.5" x 5.5")	Optional (factory built in): Single ATS Tray Feeder. Max. number of amount of pallets 2 x 15 with 12.5mm pallet pitch, pick area for all heads from tray 210mm x 325mm (8.3" x 12.8") No PCB width restriction
	Dual ATS Tray Feeder: Max. tray size: 230mm x 335mm (9.1" x 13.2") Min tray size 90mm x 140mm (3.5" x 5.5")	Optional (factory built in): Dual ATS Tray Feeder (Max. board width 330mm (13"), max. number of 8mm feeders 48, amount of pallets 4x 15 with 12.5mm pallet pitch, pick area for all heads 220mm x 312mm (8.7" x 12.3") <i>(available only on project base)</i>
	Double Shuttle Tray Sequencer: Max. tray size: 230mm x 335mm (9.1" x 13.2") Min tray size 90mm x 140mm (3.5" x 5.5")	Optional: Double Shuttle Tray Sequencer (no PCB width restrictions). Amount of pallets 4x 15 with 12.5mm pallet pitch, including inspection conveyor.
	Stick and bulk:	Many solutions possible
Maximum height pre-mounted components:	25.5mm on placement side (0.26") 30mm on non placement side (1.2")	Depending on component neighborhood
PCB Dimensions (x,y):	Min: 50 x 50mm (2.0" x 2.0 ") Max: 460 x 440mm (18" x 17.2") <i>Special applications upon request, 500 x 570mm (19.7" x 22.4")</i>	Using board clamping system
PCB Weight:	Max. 1.2 Kg Max. 2.0 Kg	Without components With components
PCB Thickness:	Min: 0.4mm (0.015") Max: 4.0mm (0.15") <i>Special applications upon request</i>	

<b>MG-8</b>		
		<b>REMARKS</b>
Non - Mountable area:	Board Top side: 3mm from rear side board edge (0.12") 3mm from front side board edge	Component height restrictions apply in the 4mm (0.40") area from front side edge depending on board thickness
	Board Bottom side: 5mm from front and rear side board edge (0.2")	Flat edge of 30mm (1.2") is required on bottom right corner for the use of the main stopper, sub and exit stopper. For Ceramic PCBs (optional) the Non-Mountable area can be different.
PCB Material:	Phenolic/FR4/Composite Materials	Ceramic PCBs requires special conveyor section (optional)
PCB positioning:	Two independent Z servo controlled push up systems	Software controlled by PCB thickness
	Two independent Board clamping units	(Max. board size 190mm)
	Push up pins	Adjustable positions
	Sub stop (PCB waiting buffer)	Fixed position
	Exit stop	Fixed position
PCB Transport height:	900mm $\pm$ 10mm (35.4" $\pm$ 0.4")	Standard
	SMEMA 953mm 12.5mm (37.5" $\pm$ 0.5")	Standard
PCB Transport direction:	Left to Right	Right to Left is optional
PCB Transport width:	Automatic	Front rail fixed Rear rail moving
PCB loading time:	Approximately 2 sec. for small boards (<190mm) and 4 sec for big boards (>190mm)	PCB loading concurrent to SMD picking and alignment
Control system:	Celeron 2.0 GHz controller	512Mb internal memory
	Windows XP operating system	
	512 Mb flash disk	
	1.44 Mb floppy drive 3.5"	
	CD-ROM	
	RS 232 Serial Interface + LAN interface	
	15" Color User Interface Flatscreen front and rear side	15" touch screen optional
LAN interface	Based on IEEE802.3u, IEEE802.3	
Communication protocol	TCP/IP, NetBEUI	
User Interface:	VGOS (Visual Graphical Operating System) Keyboard and mouse for data editing functions.	Standard
	Operational panel front and rear side	Standard

<b>MG-8</b>		
		<b>REMARKS</b>
Control system functions:	Max. 127 PCBs	12,800 comp/PCB
	# components types/PCB	255
	Max. blocks/PCB	512
	Backup and restoring data using floppy	
	Supported formats: VIOS, VIOS-TXT,YGX	VIOS: binary format VIOS-TXT: text format YGX: format (preferred)
	MIS data gathering	
	Data teaching	
	Data tracing	
	Component database	16,000 Component packages; user can define and teach vision files
	Mark database	300 Mark shapes
	SMEMA electrical interface	
	On line calibration	
	On line help functions	
Feeder lock verifier		
Machine dimensions and weight:	Length: 1650mm (5.4 ft) Height: 1850mm (6.1 ft) Width: 1562mm (5.1 ft) Weight: 1630kg (3592 Lbs)	Width including feeders; pneumatic feeders 2376mm (7.83 ft), electrical feeders 2150mm (7.05 ft)
Safety standards:	EN 292, EN 294, EN 349, EN 614, EN 1050, EN 55011, EN 61000-6-2, EN 60204-1	CE-safety is part of system design. Safety measurements are tested on each product in the factory.
	EN 301 489-1, EN 301 489-3, EN 300 330-2, EN 60950	For MG-8 with CLi feeder interface
Warning lights :	White: Emergency stop, safety cover interlock Blue light: Pick up error, out of components Green: In automatic operation	
Electric Power:	Voltage AC: 200/208/220/240/380/400/416 V ± 10 %, 3 Phase	
	Frequency: 50/60 Hz	
	Noise peak: 1,500V, 1μ sec or less	
	Consumption: 4.8 kVA max.	
	Average power consumption: 0.72KW	
	Floor: Flat, slope is 10mm or less	
Air supply:	Pressure: > 5.5 .10 <sup>5</sup> Pa (5.5 bar, 80 PSI) Quality: dust and oil free Consumption: min.120 NI/min	
Operating Temperature:	15-35° C (59° - 95° F)	Specification guaranteed: 20°-28°C (68° - 82° F)
Humidity:	20 - 90 %, no dew	
Noise:	< 78dba	
Clean Room:	Class 10,000 (10 K)	

Table 1

### 3.0 Features, Accessories and Options

#### 3.1 Features

##### **The standard-MG-8 includes the following features:**

- On the fly alignment using a vision system with a Line array camera standard equipped with a side illumination unit for BGA's,  $\mu$ BGA, CSP components.
- Placement beam with 3 Flying Nozzle Change heads (each head standard equipped with 6 nozzles). All heads have independent Z servo control and rotation motors.
- Simultaneous picking is possible by all 3 heads from any mix of tape feeders. This allows a much higher nominal placement rate and board throughput.
- Complete component range can be handled with only 6 nozzle shapes.
- Fiducial alignment camera with software controlled illumination unit (white + IR Leds), wide angle diffuser and co-axial illumination. Fiducial camera can also be used as teaching/tracing device and for Bad Mark sensing.
- Automatic width adjustment. The PCB dimension is included in the PCB data.
- Two independent board clamping systems (for PCB length < 190mm).
- Two independent Z servo controlled push up systems including push up pins, for PCB support (for PCB length < 190mm). PCB thickness is included in the PCB data.
- Substopper, allowing an additional PCB to enter the machine for reducing transport time.
- Exit Substopper, providing a buffer section.
- Automatic nozzle cleaning station for all nozzles. Three heads at once are positioned in the cleaning station and by air pressure the nozzles will be cleaned.
- Feeder indicators which provide the operator with all the essential information regarding the feeder status (easy set-up).
- Feeder lock verification system to avoid damage to the machine due to incorrectly latched feeders.
- 3.5" FDD for backup purposes.
- CD-ROM drive for software installation.
- Front and rear: 15" LCD, operation panel, keyboard and mouse.
- Component dump box.
- Operator manual, available in different languages.
- User manual.
- Service manual.
- Two empty tape bins.
- Toolset.
- First aid spare parts kit.
- CE safety.
- ESD safety.
- Electrical and Mechanical SMEMA.
- Ethernet communication port.
- RS 232 communication port.

**Standard Software features:**

- Variable XY axis speed per component.
- Datum angle functionality (especially for stick components, there is no pick angle necessary to recognize the component which results in higher output).
- User Friendly Graphical Human interface VGOS with touch screen capability.
- An On-line help function allows display of detailed descriptions of operations and functions on screen.
- Management Information System (MIS) to gather production history data.
- 4 point fiducial correction, to maintain accuracy for stretched/distorted boards.
- Template (pattern) matching for PCBs that have no fiducials.
- Different mark shapes for fiducial pair possible.
- Fiducial recovery function in case of recognition error or damaged fiducials.
- Data editing functions with the use of the fiducial camera (teaching, tracing).
- A Component database, that can hold up to 16,000 component packages, with the most frequently used components already predefined.
- A Mark database, that can hold up to 300 mark shapes, with the most frequently used mark shapes already predefined.
- Precede pick-up, allowing to pick up components before the PCB is fixed, reducing cycle time.
- Alternative feeder function, reducing operator intervention (empty feeder switching).
- Self Production Control, with use of bad marks the machine can determine which components should be placed. This is ideal for family boards.
- Automatic rework cycle to improve operator efficiency and online optimization, to keep mounting speed during production in case of empty feeders. Detected empty feeders are automatically skipped until end off programs, to allow one time replenishment.
- Product preparation can be done on the machine including basic optimization of the mount program (nozzle and feeder set-up).
- Multi-section PCBs can either be mounted block-by-block or the block data can be combined to achieve the fastest mounting sequence. In the latter case, block badmarks still remain in effect.
- Programmable retry function.
- Adaptive pick-up for automatic correction of feeder pick-up position.
- Task manager to carry out daily maintenance like automatic nozzle cleaning automatically on a pre-defined sequence.

### 3.2 Accessories and Options

<b>Accessories and options MG-8 CL/CLi</b>	
9466 920 10921	Reject belt feeder
PA 1902/00	Force control MG-8
PA 1905/03	Set up verification offline first machine
PA 1905/05	Lot traceability first machine
PA 1905/06	PDA hardware for USA
PA 1905/13	Set up verification offline second machine
PA 1905/15	Lot traceability second machine
PA 1905/16	PDA hardware for EUR
PA 1906/01	Pre empty warning first machine
PA 1906/02	Set up verification inline CLi first machine
PA 1906/04	Auto program change over first machine
PA 1906/09	Auto program change over (stand alone) first machine
PA 1906/11	Pre empty warning second machine
PA 1906/12	Set up verification inline CLi second machine
PA 1906/14	Auto program change over second machine
PA 1906/19	Auto program change over (stand alone) second machine
PA 1912/15	MG adjustment tool
PA 2505/70	Feeder exchange cart 24 pos for MG (Cli version)
PA 2505/71	FES 24 factory built in front side MG (Cli version)
PA 2505/72	FES 24 factory built in rear side MG (Cli version)
PA 2505/74	FES splicing rack 24 position
PA 2505/75	Feeder exchange cart 24 pos for MG serie cl
PA 2505/76	FES 24 factory built in front side MG CL
PA 2505/77	FES 24 factory built in rear side MG CL
PA 2505/78	Modification kit FES24 CLi for MG (front or rear side)
PA 2505/79	Modification kit FES24 CL for MG (front or rear side)
PA 2506/36	Touch screen front side for MG
PA 2506/37	Touch screen rear side for MG
PA 2506/41	Maintenance lamp for MG
PA 2696/27	Single ATS for MG (including 2 magazines with 30 pallets)
PA 2699/25	Double shuttle LCS for MG (including 4 magazines with 60 pallets)
PA 2903/27	16mm Tapefeeder 15" CL
PA 2903/29	16mm Tapefeeder 15" CLi
PA 2903/38	24mm Tapefeeder 15" CL
PA 2903/39	24mm Tapefeeder 15" CLi
PA 2903/48	32mm Tapefeeder 15" CL
PA 2903/49	32mm Tapefeeder 15" CLi
PA 2903/58	44mm Tapefeeder 15" CL
PA 2903/59	44mm Tapefeeder 15" CLi
PA 2903/68	56mm Tapefeeder 15" CL
PA 2903/69	56mm Tapefeeder 15" CLi
PA 2903/77	Tapefeeder 8x2 15" CL 0201
PA 2903/78	Tapefeeder 8x2 15" CL 0402
PA 2903/79	Tapefeeder 8x4 15" CL
PA 2903/88	Tapefeeder 12mm 15" FV/GEM CL
PA 2903/89	Tapefeeder 12mm 15" FV/GEM CLi
PA 2903/97	Tapefeeder 8x2 15" CLi 0201
PA 2903/98	Tapefeeder 8x2 15" CLi 0402
PA 2903/99	Tapefeeder 8x4 15" CLi

PA 2904/51	Gem bulk cassette feeder C0603 long
PA 2962/36	Nozzle set MG-8
PA 2963/28	Nozzle exchange station MG-8
PA 2969/31	Side view camera MG-8
PA 2969/35	3D coplanarity checker 32mm for MG
PA 2969/36	3D coplanarity checker 45mm for MG
PA 2969/37	Second line array 32mm MG
PA 2969/58	Second line array 45mm MG
PA 2969/88	Area CCD camera 55mm MG-8
PA 2981/02	Magazine rack (including 15 pallets)

Table 2

<b>Accessories and options MG-8 ITF</b>	
9466 920 10911	Reject belt feeder for ITF Type
PA 1902/00	Force control MG-8
PA 1906/09	Auto program change over (stand alone) first machine
PA 1906/19	Auto program change over (stand alone) second machine
PA 1912/15	MG adjustment tool
PA 2505/52	FES ITF cart 20 position
PA 2506/36	Touch screen front side for MG
PA 2506/37	Touch screen rear side for MG
PA 2506/41	Maintenance lamp for MG
PA 2601/01	Tape loading unit
PA 2602/01	Feeder storage cart
PA 2654/06	Tapefeeder ITF2 8mm r3
PA 2654/16	Tapefeeder ITF2 12mm r3
PA 2654/26	Tapefeeder ITF2 16mm r3
PA 2654/36	Tapefeeder ITF2 24mm r3
PA 2654/46	Tapefeeder ITF2 32mm r3
PA 2654/56	Tapefeeder ITF2 44mm r3
PA 2654/66	Tapefeeder ITF2 56mm r3
PA 2657/00	Twin tape feeder 8mm
PA 2696/27	Single ATS Tray Feeder for MG (including 2 magazines with 30 pallets)
PA 2699/25	Double shuttle Tray Sequencer for MG (including 4 magazines with 60 pallets)
PA 2923/10	Set of 10 ITF dummy feeders
PA 2962/36	Nozzle set MG-8
PA 2963/28	Nozzle exchange station MG-8
PA 2969/31	Side view camera MG-8
PA 2969/35	3D vision system 32mm for MG
PA 2969/36	3D vision system 45mm for MG
PA 2969/37	Second line array 32mm MG
PA 2969/58	Second line array 45mm MG
PA 2969/88	Area CCD camera 55mm MG-8
PA 2981/02	Magazine rack (including 15 pallets)


Table 3



### 3.3 Machine Configuration Examples

On the following pages you can find some machine configuration examples for the MG-8.


**Remark 1:** In the examples the dotted lines pictures indicate the physical position of the second line array camera, Co-planarity checker. These can be ordered as an option.




1. Second Line Array Camera
2. 3D Vision System
3. Double Shuttle Tray Sequencer
4. FES 24 position
5. Nozzle station

**Remark 2:** Standard the MG-8 FNC ITF is equipped with front side FES 20 and no rear side feederbar.

Standard all MG-8 machines are equipped with:

 nozzle cleaning station


**Example 1: MG-8 CL with Double Shuttle Tray Sequencer**



- |                |                                       |
|----------------|---------------------------------------|
| PA 1318/01     | MG-8 CL                               |
| PA 2505/76     | FES 24 factory built in front side CL |
| PA 2505/77     | FES 24 factory built in rear side CL  |
| PA 2699/25     | Double shuttle inline head LCS        |
| PA 2969/35-/36 | 3D Vision System 32 mm or 45mm for MG |
| PA 2969/37-/58 | Second line array 32mm or 45mm for MG |
| PA 2963/28     | Nozzle exchange station               |

\* Field of view of the 3-D Vision System must match the FOV of the Line Array Camera.

**Example 2: MG-8 with CLi feeders**



PA 1318/02

MG-8 CLi

PA 2505/71

FES 24 factory built in front side CLi

PA 2505/72

FES 24 factory built in rear side CLi

PA 2969/35-/36

3D Vision System 32mm or 45mm for MG\*

PA 2969/37-/58


Second line array 32mm or 45mm for MG

PA 2963/29

Nozzle exchange station

\* Field of view of the 3-D Vision System must match the FOV of the Line Array Camera

**Example 3: MG-8 with Single ATS Tray Feeder and CLI feeders**



PA 1318/02

MG-8 CLI

PA 2505/71

FES 24 factory built in front side CLI

PA 2505/72

FES 24 factory built in rear side CLI

PA 2696/27

Single ATS for MG

PA 2969/35-/36


Co-planarity checker 32mm or 45mm for MG-8\*

PA 2963/28

Nozzle exchange station

\* Field of view of the 3-D Vision System must match the FOV of the Line Array Camera

**Example 4: MG-8 ITF**




PA 1318/03  
PA 2969/35-/36  
PA 2963/28

MG-8 ITF  
3-D Vision System 32mm or 45mm for MG\*  
Nozzle exchange station

\* Field of view of the 3-D Vision System must match the FOV of the Line Array Camera


**Example 5: MG-8 ITF with Single ATS Tray Feeder**



PA 1318/03	MG-8 with ITF
PA 2696/27	sATS for MG
PA 2969/35-/36	3-D Vision System 32mm or 45mm for MG*
PA 2969/37-/58	Second line array 32mm or 45mm for MG
PA 2963/28	Nozzle exchange station

\* Field of view of the 3-D Vision System must match the FOV of the Line Array Camera

- 4.0 Mounting Heads** The MG-8 features a high precision single placement beam which carries 3 independent Z-servo FNC heads and three rotation motors. Each FNC head is equipped with 6 nozzles.
- 4.1 Configuration Head MG-8** On the beam a separate camera system is attached that monitors fiducial marks at the board, circuit and component level, using white + IR light LEDs and multi-angle diffusers to provide optimal illumination. High placement rates are achieved by simultaneous component picking which reduces head beam travel and thus shortens the mounting cycle.



*Figure 2 Configuration of head section*

The high-precision dual Y drive MG-8 features five-axis (X,Y,Z,N,R) servo control for accurate, stress-free component mounting. Direct drive, brushless AC motors controlling heavy duty lead screws allow optimal accuracy and high reliability.

<b>Specifications</b>	
Number of axis:	15
Axis configuration (AC servo):	1 x X axis
	2 x Y axis
	3 x Z axis
	3 x R axis
	3 x N axis
	1 x W (automatic width) axis
	2 x Push up plate
Pick-up error detection:	Vacuum check (256 level digital setting)
Mounting angle:	0° - 360° (0.01° step)
Number of mounting head:	3 in-line multi head, FNC
Nozzle types:	6 different shapes
Encoder resolution:	X,Y = 0.0003mm/pulse
	Phi = 0.0014°/pulse
	Z = 0.0029mm/pulse
Head position accuracy:	X = 0.004mm
	Y = 0.004mm
Speed:	X = 1,500mm/sec.
	Y = 1,500mm/sec.
Acceleration:	X = 33,400mm/sec <sup>2</sup>
	Y = 23,800mm/sec <sup>2</sup>

Table 4

- 4.2 Force Control PA 1902/00** To expand the component range of the MG-8 with press-fit through-hole components an optional force control system for all three heads is available. The force control is aire driven and adjustable for each component from 10 to 40 newton in steps of 0.1 newton.



## 5.0 Alignment

### 5.1 Line Array Camera Alignment

The high speed of the MG-8 is achieved by fast on-the-fly component alignment using a revolutionary Line Array camera system, equipped with a newly developed multi angle illumination unit, significant faster than conventional vision systems. For ultimate speed, the machine can be equipped with a second Line Array camera which reduces head beam travel and thus shortens the mounting cycle on high unique component count per board.




Figure 3 Line sensor vision principle

While moving the beam over the camera, the encoder triggers the camera to capture consecutive lines of pixels. All these lines form the total picture of the components. This picture is processed by a sophisticated vision system. The vision system algorithms inspect the components and calculate position and orientation of the components on the heads.

The SMD components are illuminated by a new developed multi angle side illumination unit which allows high speed recognition of CSP's,  $\mu$ BGA's and Flip Chips. The leads of the components are imaged on the line sensor.

Specifications	
Line array camera:	CCD 2048 x 1 pixels
Max. component size:	32mm square (1.26") or 45mm square (1.77")
Min. component size:	01005 (0402)
Min. lead pitch:	0.3mm (16 mil)
Min. lead width:	0.15mm (0.005")
Grey scale:	256 levels
Lighting:	Multi angle Fore/side illumination (red LED array) Light intensity is software controlled for each component separately
Recognition:	Reflection. Pattern recognition on all leads
Max. number of lead sides:	4
Max. number of lead groups:	2 per side
Check on:	Lead/ball pitch Lead/ball location Bent/missing leads/balls Total number of leads/balls Cumulative lead/ball pitch

Table 5

- 5.2 Single Area CCD Alignment (PA 2969/88)** An optional single area CCD camera extends the component range for the MG-8. Component illumination is performed by means of fore /reflective lighting and side illumination. The lighting source reflects the lead of QFP and the balls of BGA components on the CCD camera. The single area CCD camera grabs the image of the component in one frame and presents it to the vision system for recognition and measurement purposes.

To increase mounting accuracy for ultra fine pitch components, the MG-8 can use the Fine mode/Multi recognition alignment method. In this mode, the calculated offset of the QFP is corrected and re-checked before actual placement is performed.

Specifications	
Area CCD camera:	CCD 1600 x 1200 pixels
Max. component size:	Lead components 45mm square (1,77") Ball components 55mm square (2,17")
Min. component size:	0402 (1005)
Min. lead pitch:	0.3 mm (16 mil)
Min. lead width:	0.15mm (0.005")
Grey scale:	256 levels
Lighting:	Multi angle Fore/side illumination (red LED array) Light intensity is software controlled for each component separately
Recognition:	Reflection. Pattern recognition on all leads
Max. number of lead sides:	4
Max. number of lead groups:	2 per side
Check on:	Lead/ball pitch Lead/ball location Bent/missing leads/balls Total number of leads/balls Cumulative lead/ball pitch

Table 6

**5.3 Side View Camera (PA 2969/31)**

For quality enhancement, optionally a unique Side View camera system is available. The camera can verify chips from 01005 to 2012 presence and orientation at the nozzle in Z-direction, while the heads fly over the line array camera for X,Y,R component recognition. The Side View camera image can be used for several purposes.

Description	Function name	Details
Pick up condition:	Detection of pick up errors	Detect the pick up and checks component thickness
	Detection of abnormal pick ups	Check for tombstone picking, side picking etc.
Mounting reliability:	Component bring back after mounting	Check after mounting for component bring back
	Component bring back after component dump	Check after dumping components to prevent bring back
Maintenance:	Dirty nozzles	Checks nozzle surface for dirt

Table 7

Specifications	
Area CCD camera:	CCD 485 x 485 pixels
Grey scale:	256 levels
Illumination:	LED back light
Applicable components:	Chip and Resistor components
Minimum component:	C and R components 01005 (0402)
Maximum component:	C and R components 2012 (0805)
Maximum component thickness:	1.2mm
Applicable nozzles:	221(F) - 222(F) - and 01005 nozzle
Recognition resolution:	20 μm
Cycle time:	No extra cycle time for component pick up check with standard configuration

Table 8




Figure 4 Side View Camera

**5.4 3D Vision System (PA 2969/35, PA 2969/36)**

In combination with the standard line array camera an on-the-fly optional 3D Vision System can check the co-planarity of any leaded component or the individual ball height for any BGA component with minimal speed penalty. Combining the images of both cameras will generate a 3D image of the components, and height differences in leads or balls are measured.

<b>Specifications 3D Vision Sytem 32mm (PA 2969/35)</b>	
Line array camera:	CCD 1024 x 1 pixels
Grey scale:	256 levels
Lighting:	Multi angle Fore/side illumination. Light intensity is software controlled for each component separately
Co-planarity detection resolution:	+/- 25 µm
Applicable components:	Leaded components like SOP, QFP, connectors-E and connector NSEW. Ball components using the BGA algorithm
Maximum component size for lead component:	32mm square in normal mode 32mm width x 100mm long in fast mode
Maximum component size for ball component:	32mm square
Minimum lead pitch:	0.4mm
Minimum lead width:	0.15mm
Minimum ball pitch:	0.4mm
Minimum ball diameter:	0.25mm
Restrictions:	Leaded components max 255 leads in one direction. Maximum grid for BGA components is 64x64 J-lead components are not supported.

Table 9




Figure 5 3D Vision System (1), Line Array System (2)

<b>Specifications 3D Vision System 45mm (PA 2969/36)</b>	
Line array camera:	CCD 1024 x 1 pixels
Grey scale:	256 levels
Lighting:	Multi angle Fore/side illumination. Light intensity is software controlled for each component separately
Co-planarity detection resolution:	+/- 35 $\mu$ m
Applicable components:	Leaded components like SOP, QFP, connectors-E and connector NSEW Ball components using the BGA algorithm
Maximum component size for lead component:	45mm square in normal mode 45mm width x 100mm long in fast mode
Maximum component size for ball component:	45mm square
Minimum lead pitch:	0.5mm
Minimum lead width:	0.2mm
Minimum ball pitch:	0.5mm
Minimum ball diameter:	0.3mm
Restrictions:	Leaded components max 255 leads in one direction. Maximum grid for BGA components is 64x64 J-lead components are not supported

Table 10

<b>Specifications Cycle time</b>	
Lead components:	2-3.5 sec/comp in NORMAL mode (1 component) 1.7-2.5 sec/comp in NORMAL mode (3 components at one time) 1.5 sec/comp in FAST mode (1 component) <i>Remark: excluding recognition time for standard line array camera</i>
Ball grid components:	1-2.5 sec/comp in NORMAL mode (1 component) 1.0 sec/comp in NORMAL mode (3 components at one time) <i>Remark: excluding recognition time for standard line array camera</i>

Table 11

## 5.5 Fiducial Alignment

The MG-8 comes standard with a fiducial camera. This camera is used to compensate for variations in the position of the circuit pattern relative to the expected position. The fiducial alignment system is an opto-electronic system which performs geometric measurements of fiducial marks on the PCB in order to calculate the deviations from their expected positions. The system can use two fiducials per board. Each sub-circuit can also be aligned using two fiducials. For placement of fine-pitch components two or four local fiducials per component may be used. The individual shapes of a fiducial pair can be different to allow for maximum application flexibility. Also pattern recognition algorithms can be used on traces or pads on the PCB board for cases where fiducials are not available. The fiducial camera can also be used as a high accurate teaching device for PCB data (if CAD data is not available), automatic calibration and inspection purposes.

Specifications	
Fiducial camera:	CCD
Fiducial camera functionality:	Fiducial detection, Bad mark detection, teaching device (2 or 4 point teaching)
Fiducial illumination:	White + IR LEDs in conjunction with a wide-angle diffuser
Compensation for: (with two fiducials)	Translation Rotation Linear stretch and shrink
Compensation for: (with 2 or 4 fiducials)	Non-linear stretch and shrink
Type of compensation:	PCB , Block, Local
Fiducial size:	Max. 3.0mm (0.12") Min. 0.8mm (0.03")
Fiducial material:	Copper Gold Lead-tin
Fiducial clearance area:	2 * Fiducial size
PCB warpage at fiducial:	Max. 0.5mm (0.02")
Pattern offset:	Max. 1mm (0.04")
Number of different Fiducial pairs per PCB:	128
Number of Fiducial shapes in Mark Database:	300
Examples of Fiducials:	Solid circle (preferred) Square Triangle Donut Binary cross Bow-tie (connected) Template matching
Fiducial definition:	According CAD data

Table 12




Figure 6 Fiducial free space



\* Preferred; others possible but not preferred

Figure 7 Fiducials




Figure 8 Examples of PCB, block and local fiducials

---

## 5.6 Master Bad Mark Sensing

If the PCB contains sub-circuits, one or more of these subcircuits can be skipped for placement by giving them a "Bad Mark" on a designated position on the sub-circuit. No parts will be placed on a circuit that has a Bad Mark. Bad Mark sensing, with the use of the fiducial camera, is based on recognition of a difference in contrast in a certain area. This area can be defined in the machine software (position and area-dimensions). This gives maximum freedom in choosing the process or technique to add Bad Marks, for example:

- white or light colored labels of any dimension,
- white paint,

... or any other material that can be applied as long as it contrasts with the PCB surface.

Before checking the Bad Marks on all circuits, the Master Mark may be checked first. Presence of a Master Mark means that one or more Bad Marks are present on the circuits. This allows the machine to skip the Bad Mark sensing process for all circuits if no Bad Marks are located on the circuits, therefore, saving valuable production time.



## 6.0 Board Handling

PCB boards will be located in the machine by a double board clamping system in combination with a double independent Push-up unit equipped with adjustable Push-up pins to support the PCB.

Change over to a different board size is just a matter of seconds by using the automatic adjustment of the conveyor width and the PCB thickness (all servo controlled).




Figure 9 Push up system

A sub-stop enables an additional PCB to enter the machine while the current board is being populated. This reduces time loss during transport and is very useful when operating the machine in a flowline. An exit sub-stop, which can be seen as a transport buffer function, links the entrance sub-stop and main stopper, shortening the PCB transport time and reducing loss from inefficient operation.

For PCBs <190mm the average PCB transport time is cut in half due to the double segment PCB conveyor which makes it possible to transport two PCBs independently from each other.

When using the machine in a flowline it communicates with the unit upstream and downstream over a SMEMA-connection.




Figure 10 MG-8 Double Board Clamping system

<b>Specifications</b>	
PCB Dimensions (x,y):	Min: 50 x 50mm (2.0" x 2.0 ") Max: 460 x 440mm (18" x 17.2")
PCB Thickness:	Min: 0.4mm (0.015") Max: 4.0mm (0.15")
PCB Maximum warpage:	0.5mm up (0.02") 1.0mm down (0.04")
Maximum height pre-mounted components:  Non - Mountable area:	25mm on placement side (1.0") <i>When using the side view camera 20mm</i> 30mm on non placement side (1.2") Board Top side: 3mm from front and rear side board edge (0.12") Component height restrictions apply in the 4mm (0.16") area from front side edge depending on board thickness Board Bottom side: 5mm from front and rear side board edge (0.2")
PCB Material:	Phenolic/FR4/Composite Materials Ceramic PCB transport is optional
PCB weight:	Max. 1.2 Kg without components Max. 2.0 Kg with components
PCB positioning:	Double independent board clamping unit (for max 190mm board length) Double independent Z servo controlled push up system (software controlled by PCB thickness) Push up pins (adjustable positions) Sub stop (PCB waiting buffer) fixed position Exit stop (fixed position)
PCB Transport height:	900mm $\pm$ 10mm (35.4" $\pm$ 0.4") SMEMA 953mm $\pm$ 12.5mm (37.5" $\pm$ 0.5")
PCB Transport direction:	Left to Right standard, optional Right to Left
PCB Transport width:	Automatic
PCB Loading time:	Approximately 2 sec. for PCB $\leq$ 190mm and 4 sec. for PCB $>$ 190mm
PCB Transport:	Belt driven, two independent segments

Table 13




Figure 11 Mountable area




Figure 12 Warp of fixed PCB




Figure 13 Mountable area

**6.1 Automatic Nozzle Exchange Station (PA 2963/28)**

Optional an 18 position automatic nozzle exchange station can be installed in the MG-8.

Just six nozzle shapes are required to cover the specified SMD range. High output levels are therefore achieved, as the need for nozzle exchanges is minimal. Nozzle exchange time for one nozzle with nozzle changer is 1.25 sec and 0,2 sec for the Flying Nozzle Head. The nozzle station enables additional special nozzles to be accommodated including grippers for odd SMD components.




Figure 14 Nozzle

Nozzle 22W (01005)	Nozzle 221	Nozzle 222	Nozzle 223	Nozzle 224	Nozzle 225	Nozzle 226

Figure 15 Nozzles




Figure 16 Nozzle Exchange Station

<b>Specifications Automatic nozzle exchange station</b>		
<b>POSITION</b>	<b>MG-8 HEAD</b>	<b>NOZZLE TYPE</b>
1	1	226
2	2	226
3	3	Free / Special
4	3	226
5	1	Free / Special
6	2	Free / Special
7	2	Free / Special
8	2	Free / Special
9	3	Free / Special
10	1	Free / Special
11	1	Free / Special
12	2	Free / Special
13	3	Free / Special
14	3	Free / Special
15	1	Free / Special
16	1	Free / Special
17	2	Free / Special
18	3	Free / Special

Table 14

## 6.2 Nozzle Cleaning Station

The MG-8 comes standard with a nozzle cleaning station which can clean all heads at the same time. High pressure air is used to clean the splines and the nozzles. This will prevent the nozzle and spline to clog with dust and thus a higher and more stable pick performance and less machine down time is accomplished. The automatic cleaning action can be specified at any time interval during production or cleaning can also be done in a manual mode. To clean all nozzles on the MG-8 will take approximately 20 seconds which includes the nozzle exchange time for all applicable nozzles.

<b>Specifications</b>	
Applicable nozzles	Nozzle Type 221, 212, 223, 224, 225, 226, 01005 nozzle and the nozzle holder.
Cycle time	+/- 20 seconds for all nozzles. ( including the automatic nozzle exchange for all applicable nozzles)

Table 15

## 7.0 Component Feeding

### 7.1 Smart Feeders CLi

Depending on the machine configuration up to 96 Smart Feeders CLi (8mm) can be loaded. The smart feeders are equipped with the latest RFID technology to speed up and simplify machine setup, and to provide a real-time component inventory check. To use this RFID technology, the main machine must be equipped with CLi feederbars.

Available CLi tapefeeders		
TAPE FEEDER	FEEDING PITCH (MM)	PA#
Tape Feeder 8mm 15" for 0603 (0201) CLi	2	PA 2903/97
Tape Feeder 8mm 15" for 1005 (0402) CLi	2	PA 2903/98
Tape Feeder 8mm 15" CLi	4	PA 2903/99
Tape Feeder 12mm 15"CLi	4,8,12	PA 2903/89
Tape Feeder 16mm 15"CLi	4,8,12,16	PA 2903/29
Tape Feeder 24mm 15"CLi	4,8,12,16,20	PA 2903/39
Tape Feeder 32mm 15"CLi	8,12,16,20,24,28,32	PA 2903/49
Tape Feeder 44mm 15"CLi	8,12,16,20,24,28,32,36	PA 2903/59
Tape Feeder 56mm 15"CLi	8,12,16,20,24,28,32,36	PA 2903/69
For larger and special tape feeders such as 72mm please contact your local sales representative		

Table 16 The feeding pitch can be adjusted on the feeder side.

Feeder occupation CL and CLi	
FEEDER TYPE	REQUIRED FEEDER POSITION EQUIVALENT TO TAPE FEEDER 8MM
Tape feeder 8mm,	1
Tape feeder 8mm	1
Tape feeder 12mm, 16mm, 24mm	2-3
Tape feeder 32mm	4
Tape feeder 44mm	5
Tape feeder 56mm	6

Table 17 The above feeder conversion number may differ according to the installation combination.

## 7.2 Smart Feeder ITF

The MG-8 with ITF Smart Feeders has a fully compatible feeder platform with the GEM Xi(II) and AX Line machines. On the standard MG-8 with ITF Feeder Interface 40 8mm ITF Smart Feeders can be loaded. With the use of the ITF Twin Tape Feeder 80 code numbers can be loaded.

ITF Smart Feeders are available for 8 up to 56mm tape widths. The feeders can be loaded with 13 inch tape reels (optional 15" is available). ITF Smart Feeders are motor driven mechanism allowing a highly reliable uninterrupted feeding process.

To prevent incorrect feeder latching, a laser-based verification system is used. To load the tapes into the ITF Smart Feeders a Tape Loading Unit is required. The TLU can be used without main power supply, a battery pack (12V DC) allows "stand alone" operation for about 8 hours.




Figure 17 Smart Tape Feeder (ITF)

Available tape feeders		
TAPE FEEDER	FEEDING INDEX (MM)	PA#
ITF 8mm	2,4,8,12,16,20,24,28,32,40,44,48,52,56	PA 2654/06
ITF 12mm	2,4,8,12,16,20,24,28,32,40,44,48,52,56	PA 2654/16
ITF 16mm	2,4,8,12,16,20,24,28,32,40,44,48,52,56	PA 2654/26
ITF 24mm	2,4,8,12,16,20,24,28,32,40,44,48,52,56	PA 2654/36
ITF 32mm	2,4,8,12,16,20,24,28,32,40,44,48,52,56	PA 2654/46
ITF 44mm	2,4,8,12,16,20,24,28,32,40,44,48,52,56	PA 2654/56
ITF 56mm	2,4,8,12,16,20,24,28,32,40,44,48,52,56	PA 2654/66
Twin Tape feeder 8mm	2,4,8,12	PA 2657/00

Table 18 The feeding pitch can be adjusted on the feeder side



Feeder occupation	
FEEDER TYPE	FEEDER SLOTS OCCUPIED
Tape feeder 8mm	1
Tape feeder 12mm	2
Tape feeder 16mm	2
Tape feeder 24mm	2
Tape feeder 32mm	3
Tape feeder 44mm	4
Tape feeder 56mm	4

Table 19 The above feeder conversion number may differ according to the feeder combination.

The MG-8 comes standard with pneumatic CL feeders which are compatible with all existing GEM models. Depending on the machine configuration up to 96 tape feeders (8mm) can be loaded. The tape feeder design allows simultaneous picking from any mix of tape feeders ranging from 8 to 56mm. To achieve high speed feeding all feeder types are air driven. To prevent incorrect feeder latching, a laser-based verification system is used.




Figure 18 Pneumatic Tape feeder

Available CL tafeeder		
TAPE FEEDER	FEEDING PITCH (MM)	PA#
Tape Feeder 8mm 15" for 0603 (0201) component CL	2	PA 2903/77
Tape Feeder 8mm 15" for 1005 (0402) CL	2	PA 2903/78
Tape Feeder 8mm 15" CL	4	PA 2903/79
Tape Feeder 12mm 15"CL	4,8,12	PA 2903/88
Tape Feeder 16mm 15"CL	4,8,12,16	PA 2903/27
Tape Feeder 24mm 15"CL	4,8,12,16,20	PA 2903/38
Tape Feeder 32mm 15"CL	8,12,16,20,24,28,32	PA 2903/41
Tape Feeder 44mm 15"CL	8,12,16,20,24,28,32,36	PA 2903/51
Tape Feeder 56mm 15"CL	8,12,16,20,24,28,32,36	PA 2903/68
For larger and special tape feeders such as 72mm please contact your local sales representative		

Table 20 The feeding pitch can be adjusted on the feeder side

### 7.3 Feeder Indicators

The MG-8 with CL and CLi feeder interface are standard equipped with feeder LED indicators. The feeder indicators provide the operator with all essential information regarding feeder status. With the use of 3 colors; Green, Yellow and Red the status will be indicated.

	ON	BLINKING
GREEN	Setup OK	
YELLOW	Error (Pickup, Recognition)	Warning
RED	Setup Not Good, Empty	Navigation (Change, Attach)

Table 21

### 7.4 Double Shuttle Tray Sequencer (PA 2699/25)

The Double Shuttle Tray Sequencer is an auxiliary unit for feeding parts from trays. This feeder can hold a maximum of 60 pallets (in 4 magazines), each being able to hold different trays. Pallets and magazines are compatible within MG-8 trayfeeders.




Figure 19 Double Shuttle Tray Sequencer

Two components are picked up from the tray with a 2 in-line head shuttle. This shuttle then moves into the machine where both components are placed on a temporary station. This station can move up and down so that the MG-8 can pickup the components. The parts are then aligned by vision and placed on the PCB. At the same moment when the components are picked by the MG-8 placement head a second shuttle will supply the next components while minimizing any feeding delays.

The component feeding time of the Double Shuttle Tray Sequencer is 4 seconds for 2 parts when using the same tray (pallet 1) and 8 seconds when changing the tray (pallet 30). However, in practice no time is lost because of the simultaneous operation of Tray sequencer and MG-8: while the machine is picking from on-board feeders, the 2 shuttles bring in new components. A part that is rejected by vision will be placed back on a reject belt feeder which means no loss of expensive parts.

The PCB conveyor on the Double Shuttle Tray Sequencer offers the possibility for visual PCB inspection.

- The tray area is fixed and separated into four sections with each 15 pallets.
- A buffer conveyor is standard equipped, so a reflow oven can be connected without additional conveyors.

<b>Double Shuttle Tray Sequencer specifications (PA 2699/25)</b>	
<b>GENERAL</b>	
Max. Tray size (L x W):	335mm x 230mm (13.2" x 9.1")
Min. Tray size (L x W):	140mm x 90mm (5.5" x 3.5")
Component feeding time:	4 sec. for 2 parts (picking from pallet 1) 8 sec. for 2 parts (picking one from pallet 1 and one from pallet 30)
Power and air supply:	Delivered by MG-8
Double Shuttle Tray Sequencer dimensions:	Length: 1,200mm (3.9 ft) Height: 1,006mm (3.3 ft) (with top cover open 1530mm (5.2 ft)) Width: 1,482 mm (4.8 ft) (with door open 1,722mm (5.8 ft))
MG-8 + Tray Feeder Sequencer dimensions:	Length: 2,855mm (9.3 ft) Height: 1,850mm (6.1 ft) Width: 1,650mm (5.6 ft) (with door open and feeders on MG-8 (2,160mm (7.3 ft))
Weight:	± 380 kg (837 Lbs)
<b>APPLICABLE COMPONENTS</b>	
Min. Component dimension:	10mm x 10mm (0.25" x 0.25") Mold size
Max. Component dimension:	45mm x 45mm (1.8" x 1.8")
Max. Tray height included component height:	8.5mm (0.33") from pallets at pitch of 12.5mm (0.5"), total 15 pallets possible per magazine
	16mm (0.63") from pallets at pitch of 25mm (0.98"), total 7x pallets possible per magazine
<b>FEED CAPACITY</b>	
Number of shuttles:	2
Number of heads on each shuttle:	2 (with a pitch of 48mm)
<b>STANDARD COMPONENT CAPACITY</b>	
Max. number of component types:	60 (60 x 1 Jedec tray)
Number of pallets:	Standard 4 magazines each with 15 pallets included (additional magazines available PA 2981/02)

Table 22

## 7.5 Single ATS Tray Feeder (PA 2696/27)

The Single ATS Tray Feeder is directly connected to the rear of the machine, allowing high-speed feeding of tray components and direct picking from tray. The feeder is equipped with 2 magazines each containing a maximum of 15 pallets, each being able to hold different trays. The magazines are moved with a lift mechanism. Pallet indicators provide easy setup during initial setup or changeover. There is no PCB width restriction with the use of the Single ATS Tray Feeder.




Figure 20 Single ATS Tray Feeder (2696/27)

The maximum pallet exchange time for the Single ATS Tray feeder is 5 seconds. However, in practice no time is lost because of the simultaneous operation of the Single ATS Tray feeder and MG-8; while the machine is picking from on-board feeders, the Single ATS Tray Feeder brings in new components.

A part rejected by vision will be placed back in its original tray position; this means no loss of expensive parts.

The Single ATS Tray Feeder allows for rapid sequential picking of parts directly from the tray on all 3 heads for IC/QFP shooting applications.

<b>Single ATS Tray Feeder specifications (PA 2696/27)</b>	
<b>GENERAL</b>	
Max. Tray size (L x W):	335mm x 230mm (13.2" x 9.1")
Min. Tray size (L x W):	140mm x 90mm (5.5" x 3.5")
Pallet exchange time:	Changing from magazine 1, pallet 1 to 15; 4 seconds Changing from magazine 1, pallet 1 to magazine 2; 3.5 seconds Changing from magazine 1, pallet 1 to magazine 2, pallet 15; 5 seconds
Weight:	± 140 kg (308 Lbs) without hook
Power and air supply:	Supplied by MG-8
MG-1 + Single ATS Tray feeder dimensions:	Length: 1,650mm (5.5 ft) Height: 1,850mm (6.2 ft) Width: 1,870mm (6.2 ft) (with ATS 20 door open, 2,115mm (7.2 ft))
Maximum board width:	440mm (17.2")
Maximum amount of feeders on MG-8:	2 x 24 + 20 = 68 or 2 x 20 = 40 for ITF
<b>APPLICABLE COMPONENTS</b>	
Max. Tray height including component height:	8.5mm (0.33") from pallets at pitch of 12.5mm (0.49"), total 15 pallets possible per magazine 20mm (0.79") from pallets at pitch of 25mm (0.98"), total 7 pallets possible per magazine
Min. Component dimension:	6mm x 6mm (0.24" x 0.24") mold size
Max. Component dimension:	45mm x 45mm (1.8" x 1.8")
<b>STANDARD COMPONENT CAPACITY</b>	
Max. number of component types:	30 (30 x 1 Jedec tray)
Number of pallets:	Standard 2 magazines each with 15 pallets included (additional magazines available PA 2981/02)

Table 23

## 7.6 Double ATS Tray Feeder (PA 2696/28)

The Dual ATS Tray Feeder is a new additional internal pallet sequencer build into the machine frame on the rear side allowing high-speed feeding of tray components. The feeder is equipped with 4 magazines each containing a maximum of 15 pallets, each being able to hold different trays. The tray area is fixed and separated into four sections with each 15 pallets. Pallet indicators provide easy set-up during initial setup or changeover. The maximum PCB width is restricted to 330mm (13").




Figure 21 Double ATS Tray Feeder (rear side MG-8)

The maximum pallet exchange time for the Dual ATS Tray feeder is 5.6 seconds. However, in practice no time is lost because of the simultaneous operation of the Dual ATS Tray Feeder and MG-8; while the machine is picking from on-board feeders, the Dual ATS Tray Feeder brings in new components.

A part rejected by vision will be placed back in its original tray position; this means no loss of expensive parts.

<b>Dual ATS Tray Feeder specifications (PA 2696/28)</b>	
<b>GENERAL</b>	
Max. Tray size (L x W):	335mm x 230mm (13.2" x 9.1")
Min. Tray size (L x W):	140mm x 90mm (5.5" x 3.5")
Pallet exchange time:	Changing from magazine 1, pallet 1 to 15; 4 seconds
	Changing from magazine 1, pallet 1 to 2; 3.5 seconds
	Changing from magazine 1, pallet 1 to magazine 2, pallet 15; 5 seconds
Power and air supply:	Delivered by MG-8
MG-8 + wATS dimensions:	Length: 2,855mm (9.3 ft) Height: 1,850mm (6.1 ft) Width: 1,850mm (6.1 ft) (with door open and feeders on MG-8 (2,121mm (7.2 ft))
Weight:	± 1,850 kg (4075 Lbs)
<b>APPLICABLE COMPONENTS</b>	
Min. Component dimension:	6mm x 6 mm (0.24" x 0.24") Mold size
Max. Component dimension:	45mm x 45mm (1.8" x 1.8")
Max. Tray height including component height:	8.5mm (0.33") from pallets at pitch of 12.5mm (0.5"), total 15 pallets possible per magazine
	16mm (0.63") from pallets at pitch of 25mm (0.98"), total 7x pallets possible per magazine
<b>STANDARD COMPONENT CAPACITY</b>	
Max. number of component types:	60 (60 x 1 Jedec tray)
Number of pallets:	Standard 4 magazines each with 15 pallets included (additional magazines available PA 2981/02)

Table 24







## 7.7 Pallet Indicators

The Double Shuttle Tray Sequencer, Single ATS and Dual ATS Tray Feeder are standard equipped with pallet LED indicators. The pallet indicators provide the operator with all essential information regarding pallet status. With the use of 3 colors; Green, Yellow and Red the status will be indicated.










	<b>ON</b>	<b>BLINKING</b>
GREEN	Setup OK	
YELLOW	Error (Pickup, Recognition)	Warning
RED	Setup Not Good, Empty	Navigation (Change, Attach)

Table 25

- 7.8 Mountable Components & Required Nozzles MG-8** Just six nozzle shapes are required to cover the specified SMD range. High output levels are therefore achieved, as the need for nozzle exchanges is minimal.

Component		Dimensions (mm)			Required nozzle Type
		L	W	T	
	Solid resistor	0.4	0.2	0.2	Special nozzle on request
		0.60	0.30	0.25	221F
		1.00	0.50	0.50	221F
		1.60	0.80	0.50	222F
		2.00	1.25	0.50	222F
		3.20	1.60	0.60	222F
	Solid resistor	2.00	$\phi$ 1.25		222F
		3.45	$\phi$ 1.35		222F
		5.9	$\phi$ 2.2		222F
	Multi-layered ceramic capacitor	0.4	0.2	0.2	Special nozzle on request
		0.6	0.3	0.3	221F
		1.0	0.5	0.5	221F
		1.50	0.80	0.80	222F
		2.00	1.25	1.25	222F
		3.20	1.60	1.25	222F
		3.20~4.50	2.50~3.20	1.50~1.90	223F
5.60	5.00	1.90	223F		
	MELF ceramic capacitor	3.40	$\phi$ 1.50		223F
		5.9	$\phi$ 2.2		226F 226A
	Tantalum electrolytic capacitor	2.90	1.60	1.60	222F
		3.80	2.90	1.60	223F
		4.70	2.60	2.10	223F
		6.00	3.20	2.50	223F
		7.30	4.30	2.80	223F
	Aluminium electrolytic capacitor	4.3	4.3	5.7	223F
		6.6	6.6	5.7	223F
		10	10	10.5	224F



Component	Dimensions (mm)			Required nozzle Type
	L	W	T	
 Chip film capacitor	7.3	5.3	3.25	223F
 Chip inductor	3.2	2.5	2.0	2234F
	4.5	3.2	3.2	223F
 Semi-variable resistor	4.5	3.8	2.4	223F
 Transistor (SOT)	2.90	1.5	1.10	222F
	4.0	3	1.8	223F
 Power transistor	4.6	2.6	1.6	223F
 SOP (6 ~ 28 pin)	5.00	4.50	1.50	223F
	7.60	4.50	1.50	223F
	10.10	4.50	1.50	223F
	12.60	5.70	1.50	223F
	15.30	7.50	2.00	224F
	17.80	7.50	2.00	224F
 PLCC	∅ 5~16			223F
	∅ 15~20			224F
	∅ 15~32			224F
	∅ 32~45			225F
 QFP	∅ 5~16			224F
	∅ 15~20			224F
	∅ 15~32			224F
	∅ 32~45			225F
 BGA	∅ 10~26			224F
	∅ 10~30			224F
	∅ 32~45			225F
	∅ 45~55			225F



Component		Dimensions (mm)			Required nozzle Type
		L	W	T	
	SOJ (20~42 pin)	∅ 10~20			223F
		∅ 15~30			224F
		∅ 32~45			225F
	TSOP (20~32 pin)	∅ 10~20			223F
		∅ 15~30			224F
		∅ 32~45			225F

Table 26 For information on CSP, BGA, bare chip and other types of components, please consult your local sales representative.

**8.0 Feederbar Exchange System**

Systems are available depending on the feeder type chosen.

**8.1 PA 2505/70**

The Feederbar Exchange System (FES) allows fast change-over by switching the complete 24 position CLi feederbar on a MG-8.




Figure 22 MG-8 CLi FES-24 Cart

Feederbars are mounted on carts for off-line feeder set-up. These carts are easily moved from set-up area to the mounting machines and back. This option is available for the front (PA 2505/71) and rear side (PA 2505/72) of the machine. An empty tape bin will be delivered with each FES cart.

<b>FES 24 CLi Specifications</b>	
	<b>PA 2505/70</b>
FES change over time:	≤ 60 sec.
FES repeatability:	Pick position ≤ 0.05mm
Applicable feeders:	Tape, stick, bulk feeders
Number of feeders on FES carriage:	8mm: 24 feeders 12/16mm: 11 feeders 24mm: 8 feeders 32mm: 7 feeders 44mm: 5 feeders 56mm: 4 feeders Stick: depends on stick dimensions
Air and Electrical interface:	Quick coupling (one action)
Electrical power:	Supplied by main system
Air supply:	Supplied by main system

FES 20 dimensions, stand alone without feeders:	Length: 785mm (2.59 ft) Width: 515mm (1.70 ft) Height: 1000mm (3.3 ft)
Weight without feeders:	65 kg (143 Lbs)
Tape waste bin :	Included

Table 27

- 8.2 PA 2505/75** The Feederbar Exchange System (FES) allows fast change-over by switching the complete 24 position CL feederbar on a MG-8.




Figure 23 MG-8 CL FES-24 Cart

Feederbars are mounted on carts for off-line feeder set-up. These carts are easily moved from set-up area to the mounting machines and back. This option is available for the front (PA 2505/76) and rear side (PA 2505/77) of the machine. An empty tape bin will be delivered with each FES cart.

<b>FES 24 CL Specifications</b>	
<b>PA 2505/75</b>	
FES change over time:	≤ 60 sec.
FES repeatability:	Pick position ≤ 0.05 mm
Applicable feeders:	Tape, stick, bulk feeders
Number of feeders on FES carriage:	8mm: 24 feeders 12/16mm: 11 feeders 24mm: 8 feeders 32mm: 7 feeders 44mm: 5 feeders 56mm: 4 feeders Stick: depends on stick dimensions
Air and Electrical interface:	Quick coupling (one action)
Electrical power:	Supplied by main system
Air supply:	Supplied by main system
FES 24 dimensions, stand alone without feeders:	Length: 785mm (2.59 ft) Width: 515mm (1.70 ft) Height: 1,000mm (3.3 ft)
Weight without feeders:	65 kg (143 Lbs)
Tape waste bin :	Included

Table 28

- 8.3 PA 2505/52** The Feederbar Exchange System (FES) allows fast change-over by switching the complete 20 position feederbar on a MG-8 with ITF feeders.




Figure 24 MG-8 ITF FES-20 Cart

The Feederbar Exchange System (FES) allows fast change-over by switching the complete 20 position feederbar on a MG-8 with ITF feeders.

Feederbars are mounted on carts for off-line feeder set-up. These carts are easily moved from set-up area to the mounting machines and back. The MG-8 ITF is standard equipped with front side feederbar exchange system. The MG-8 FES 20 ITF carts are fully compatible with those of the Topaz-Xi, Emerald-Xi, Topaz-Xi II and Emerald-Xi II. An empty tape bin will be delivered with each FES cart.

<b>FES 20 Specifications</b>	
	<b>PA 2505/52</b>
FES change over time:	≤ 60 sec.
FES accuracy from FES cart fiducials	X= +/- 0.05mm
to pick position ( $\mu + 3\sigma$ ):	Y= +/- 0.05mm
	Z = +/- 0.10
Applicable feeders:	ITF tape feeders
	ITF stick feeders
Number of feeders on FES carriage:	8mm: 20 feeders
	12/16mm: 9 feeders
	24mm: 10 feeders
	32mm: 6 feeders
	44mm: 5 feeders
	56mm: 4 feeders
	Stick: depends on stick dimensions
Air and Electrical interface:	Quick coupling (one action)
Electrical power:	Supplied by main system
Air supply:	No air supply to feeders
FES 20 dimensions, stand alone	Length: 820 mm (2.7 ft)
without feeders:	Width: 470 mm (1.55ft)
	Height: 1050 mm (3.44 ft)
Weight without feeders:	55 kg (121 Lbs)
Tape waste bin :	Included
Compatibility:	Topaz-Xi, Emerald-Xi, Topaz-Xi <sup>ii</sup> and Emerald-Xi <sup>ii</sup> , MG-1 with ITF
Min. component size:	0402 (1.0mm x 0.5mm)
	Smaller components should be used with pick-up teaching function

Table 29

9.0 MG-8 Summary

	Model	MG-8	MG-8	MG-8
		PA1318/01	PA 1318/02	PA 1318/03
<b>Head</b>	Flying Nozzle Change Head (FNC)	o	o	o
	Nozzle Exchange station	#	#	#
	Nozzle cleaning station	o	o	o
	Special order nozzles	*	*	*
	Force control	#	#	#
<b>Recognition system</b>	Line Array camera 45mm	o	o	o
	Line Array camera 32mm	*	*	*
	Second line ary camera	#	#	#
	3D co-planarity checker	#	#	#
	Side view camera	#	#	#
	Fiducial camera	o	o	o
<b>Feeding</b>	Pneumatic Tape Feeder CL	o	na	na
	Pneumatic Tape Feeder CLi (RFID)	na	o	na
	Intelligent tapefeeder	na	na	o
	Bulk Feeder	#	#	#
	Stick Feeder	#	#	#
	Single ATS trayfeeder (sATS)	#	#	#
	Double ATS trayfeeder (wATS)	*	*	*
	Double Shuttle inline head Tray Feeder (LCS)	#	#	#
	Reject station	#	#	#
	Feeder Exchange System (FES 24)	#	#	na
Feeder Exchange System (FES 20) ITF	na	na	o	
<b>PCB positioning/transport</b>	Main Stopper	o	o	o
	Double Board Clamp System	o	o	o
	Z servo controlled double Push Up Plate	o	o	o
	Adjustable Push up pins	o	o	o
	Entrance Sub Stopper	o	o	o
	Exit Sub Stopper	o	o	o
	Automatic Width Adjustment	o	o	o
	High Speed soft-stop conveyor	o	o	o
	Reverse transfer Right to Left	#	#	#
	Ceramic PCBs	#	#	#
Special sized PCBs	*	*	*	
<b>Safety</b>	Feeder Floating Detection	o	o	o
	Feeder indicators	o	o	na
	Conveyor Entrance/Exit covers	o	o	o
	Safety cover for feeder exchange	o	o	o
	Dummy Feeders	o	o	o
	Safety specifications according CE standards	o	o	o
	Spare parts kit + tools	o	o	o
	SMEMA kit	o	o	o
	Front and rear anti-static covers	o	o	o
Signal tower + warning buzzer	o	o	o	
<b>Software</b>	Windows XP Graphical User interface	o	o	o
	Multiple Accuracy Compensation System	o	o	o
	Fiducial Recovery function	o	o	o
	Bad Mark / Master Mark Sensing	o	o	o
	On-line teaching	o	o	o
	Alternative Feeder Function	o	o	o
	Self Production Control	o	o	o
	Variable XY axis speed per component	o	o	o
	On-line Help function	o	o	o
	Management Information System	o	o	o
	Template (patten matching)	o	o	o
Automatic rework cycle	o	o	o	
On-line data generator	o	o	o	

Table 30

o = Standard  
 # = Optional  
 \* = Special order